


Proxess MX Wireless Mortise Lock

The **Proxess MX mortise lock** extends the family of e-locks to include locks requiring mortise prep and deadbolt applications. Like other Proxess products, the MX mortise lock is equipped with Bluetooth (BLE) and 13.56 Mhz RF high-frequency technologies to communicate with our most advanced contactless smart cards, mobile apps, and BLE bridges, creating automatic updates to the system software.

The MX mortise lock saves customers significant time and money by combining all components of a typical access control system (lock, reader, and request-to-exit) in one easy-to-install device. Because the device is equipped with BLE wireless technology, costly wiring installations can be avoided in most applications. Imagine the cost of time and labor saved when compared to traditional EAC door installations.

Proxess supplies wireless locks which provide the features of access control systems at a price more commonly associated with standard, industrial Grade 1 locks. Proxess provides intelligent lock solutions appropriate for all commercial doors, creating significantly more security through the instant electronic “rekey” of locks, time schedules, and audit trails to verify who has entered doors. Proxess mortise locks also utilize four levels of Lockdown features, making them ideal for school lockdown, office buildings, multi-family housing, and most commercial applications.

To design a system that most economically meets your security requirements, reference the System Design Guide under the Solutions tab on the Proxess.com website or call the Proxess office at 303.317.6656 and ask to talk with the Field Engineer or Proxess dealer in your area.



FEATURES & BENEFITS






	<p>Bluetooth technology on board allows lock networking, mobile credentials, and emergency lockdown upgrades.</p>
	<p>Unlike mechanical locks, Administrators can decide WHO may enter doors, WHEN users are authorized to enter doors (time schedule), and receive an audit trail of these events.</p>
	<p>Locks can be installed in minutes.</p>
	<p>ANSI Grade 1 Simple, field-reversible lever handing in seconds.</p>
	<p>Emergency mechanical key override includes pick-resistant removable core and patented process which monitors emergency mechanical key operation.</p>
	<p>4 Levels of Connectivity allows customers to migrate from communicating at the door, through smart card linkage, BLE wireless bridges, or online.</p>
	<p>Utilizes Mifare DESFire EV2, the latest and most advanced RFID contactless smart credential technology. Proxess further protects credential communication by utilizing six layers of security, including 128bit AES encryption and custom electronic keying.</p>
	<p>Mobile programming device (MPD) updates lock without cumbersome device programming. Administrator can forward programming capability to other MPDs on the other side of campus or around the world utilizing Proxess' <i>Proxy/Q</i> technology.</p>
	<p>Downloadable software app on phone programs locks and is upgradeable to a robust server-based software without changes to the lock.</p>

SPECIFICATIONS

Certifications:	ANSI 156.2 and ANSI 156.25 Grade 1; UL10C Fire-Rated; FCC; RoHS, UL294, ULC Canada	<i>UL Pending</i>
Connectivity:	<ul style="list-style-type: none"> • Bluetooth Communication Up to 100 Feet • RF and Network-on-Card RF • Mobile Programming Device Up to 100 Feet 	
Users:	Unlimited	
Audits:	5000, Rotating / First-in-First-out (FIFO)	
Time Schedules:	64+	
Door Thickness:	1 3/4" to 2"	
Strike:	Standard ANSI 1 1/4" x 4"; Optional 1 3/16" Lipped T-strike	
Escutcheon Dimensions:	<ul style="list-style-type: none"> • Outside = 5.5" X 3.62" X 1.33" (140mm x 92mm X 33.7mm) • Inside = 7.56" x 3.5" x 1.33" (192mm x 88.9mm x 33.7mm) 	
Operating Temperature:	ANSI Standard -31° to 151° F (-35° to 66° C)	
Functions:	Non-electronic: Passage, privacy	Electronic Programmable Functions <ul style="list-style-type: none"> • Latch only: Entrance, classroom, storefront, and storeroom • Latch & Deadbolt: Entrance, dormitory, hotel, and storeroom • Other custom electronic functions upon request
Emergency Mechanical Keying:	Standard 6-pin or 7-pin, Special Pick-Resistant, Interchangeable Core, Custom Keying with Monitored Emergency Key Override	
Lock Reader:	RFID 13.56 MHz, ISO 14443A, BLE	
Visual and Audio Communications:	LED (Tri-Color) Indicator Light and Audio Indicator	
Credentials:	Multi-Application, Mifare DESFire EV2®; BLE Mobile Credentials	
Credential Security:	DESFire EV2; 128-bit AES Encryption	
Indoor/Outdoor:	ANSI Indoor/Outdoor Certified 156.2 Indoor/Outdoor, Normal Operating Humidity: 0 – 100%, Non-Condensation; Optional Outdoor UL IP 65 Equivalent	
Warranty:	10-Year Mechanical Warranty; 2-Year Limited Electronic Warranty	

HOW TO ORDER

NOTE: Customer may leave steps blank if standard option is preferred for that step in the ordering process.

STEP:	1 SERIES	2 FUNCTION	3 LEVER STYLE	4 FINISH	5 KEYING
Standard Product #	MX	STB	8	626	KA
Standard description	MX Mortise lock for mortise cut-out door	STB Standard bolt function (programmable)	8 Curved return	626 Satin chrome	KA Keyed alike
Option description		STL Standard latch function	 6 Angled return	 606 Satin brass	KI Keyed individually
				 690 Dark bronze (613 equivalent)	LC Less core
				 <i>Other finishes upon request</i>	CK Custom keying

STEP 6: SPECIFIC INSTRUCTIONS

- **Door thickness**
If door thickness is significantly thicker than 1 3/4", a special length cylinder may be required
- **Handing**
MX is easily reversible in the field by simply rotating the lever 180 degrees before installation
- **Specify 'W'** when both exterior and interior trim are exposed to outside environments

To order software, go to the **Support and Data Sheets** tab on the Proxess website, then proceed to the **Download** tab to choose your software. Typically, you would choose **LoxIQ** software for small, phone-based systems (50 users/doors) and **ProxessIQ** server-based software for large systems. However, LoxIQ doors and users are limited only by the practicality of entering info on a phone vs server software.